

# P1300

Industry leading PCI-PED security.



## Product Data

The Hypercom P1300 PCI-approved PIN entry device is designed to meet the PCI-PED security standards for PIN entry, providing merchants with low-cost migration to newly imposed security guidelines. It is compatible with all Hypercom product families and features flexible communications options for rapid integration with electronic cash register (ECR) systems.

## Key Features

- Low-cost PCI-PED approved PIN entry device
- Triple DES certified for DUKPT
- 2x16 alphanumeric LCD display
- Intuitive user interface with color-coded Cancel, Clear and Enter keys
- Screen-addressable function keys provide more control for users
- Multiple communication options for connecting to existing POS equipment
- Plug-and-play software for use with current Hypercom terminals
- Compatible with Hypercom Key Loading and Management (HKLM) system
- Small, ergonomic design fits comfortably in customers' hands

Whether you're looking for a reliable payment terminal, innovative, value-add technology, or a complete electronic transaction management system, Hypercom can deliver. Our product portfolio ranges from basic credit authorization to full transaction transport and more. Hypercom is more than a one-stop shop for payment terminals, it's a provider of complete, end-to-end transaction solutions that expand the possibilities at the POS in ways that translate to greater profits.

# P1300

Industry leading PCI-PED security.

## Technical Specifications:

### Keypad

- Elastomeric: 16 keys, water splash-resistant, hard keycaps

### Display

- 2 x 16 characters

### Communications

- RS-422 PIN pad port (standard)
- RS-232 or USB client (optional)

### Power

- 5v @ 240mA - 12v @ 100mA (standard)

### Security

- Physical: PCI-PED approved; intrusion detection

### Encryption

- DES: PIN-ANSI X9.8, MAC-ANSI X9.9
- Triple DES: ANSI X9.52
- Key management: DUKPT, ANSI X9.24 Part 1

### Footprint

- 3.31 in x 6.02 in x 1.30 in/84.0 cm x 153.0 cm x 33.0 cm

### Weight

- .40 lbs/0.18 kg

### Environment

- Temperature: 0-45°C/32-115°F
- Humidity: Max 85%, non-condensing
- ESD: 12,000 volts

### Reliability

- 100,000 hours (MTBF calculated)

## Cost-Effective

- Simple, functional design provides low-cost migration to new PCI-PED security standards
- Can be equipped with Hypercom standard RS-422, RS-232 or USB Client for easy integration with existing POS equipment
- Operates with any Hypercom terminal that uses DUKPT encryption automatically by simply plugging the unit into the payment device's PIN pad port
- Uses the same key loading system (HKLM) as previous generation PIN pads to save customers time and money on new equipment and training.

## Performance

- Provides clear instructions to the user facilitating the transaction process
- Features customary keypad layout with easily identifiable function keys that are fully compliant with industry standards
- Includes three soft keys below the screen that provide users more control over the transaction process
- Compact design ensures users can easily handle the unit and allows them freedom to further shield their PIN entry with their body or hand.

## Security

- Supports both DES and Triple DES DUKPT encryption to protect valuable cardholder PIN information
- Tamper-proof design meets stringent security standards that safeguard the device from external attacks
- Meets new PCI-PED security guidelines.

### World Headquarters:

Hypercom Corporation | 2851 W. Kathleen Road, Phoenix, Arizona 85053, USA  
Tel: +1.602.504.5000 | Fax: +1.602.504.4655 | Web: [www.hypercom.com](http://www.hypercom.com)

### Global Locations:

North America | Latin America | Asia/Pacific Rim | Europe | Middle East | Africa | Australia